



# EQUAL FLEXX

MORE MILES. LESS FUEL

## TRUCK TIRES

Tire Size		Wheel Position	
		Single	Dual
7.50	R18	E-4 oz.	D-6 oz.
8.00	R19.5	D-6 oz.	C-8 oz.
9.00	R19.5	D-6 oz.	C-8 oz.
18.00	R19.5	W-16 oz.	
225/70	R19.5	D-6 oz.	C-8 oz.
245/70	R19.5	D-6 oz.	C-8 oz.
265/70	R19.5	D-6 oz.	C-8 oz.
275/70	R19.5	C-8 oz.	B-10 oz.
285/70	R19.5	C-8 oz.	B-10 oz.
295/70	R19.5	C-8 oz.	B-10 oz.
305/70	R19.5	B-10 oz.	A-12oz.
280/75	R19.5	C-8 oz.	B-10 oz.
445/65	R19.5	W-16 oz.	
525/65	R20.5	B+C+C=26 oz.	
615/65	R20.5	A+A+B = 34 oz.	
7.50	R20	C-8 oz.	B-10 oz.
8.25	R20	C-8 oz.	B-10 oz.
9.00	R20	B-10 oz.	A-12oz.
10.00	R20	B-10 oz.	A-12oz.
11.00	R20	A-12oz.	V-14 oz.
12.00	R20	A-12oz.	V-14 oz.
12.50	R20	A-12oz.	V-14 oz.
13/80	R20	A-12oz.	V- 14 oz.
14/80	R20	V- 14 oz.	W-16 oz.
14.00	R20	W-16 oz.	
16.00	R20	B+B = 20 oz.	
10.00	R22	B-10 oz.	A-12 oz.
11.00	R22	A-12oz.	V-14 oz.
9.00	R22.5	C-8 oz.	B-10 oz.
10.00	R22.5	B-10 oz.	A-12 oz.
11.00	R22.5	B-10 oz.	A-12 oz.
12.00	R22.5	A-12 oz.	V-14 oz.
275/50	R22.5	B-10 oz.	A-12 oz.

Tire Size		Wheel Position	
		Single	Dual
235/70	R22.5	D-6 oz.	C-8 oz.
255/70	R22.5	C-8 oz.	B-10 oz.
11/70	R22.5	B-10 oz.	A-12 oz.
265/70	R22.5	C-8 oz.	B-10 oz.
295/60	R22.5	B-10 oz.	A-12 oz.
275/70	R22.5	B-10 oz.	A-12 oz.
305/70	R22.5	B-10 oz.	A-12 oz.
365/70	R22.5	V-14 oz.	
315/70	R22.5	B-10 oz.	A-12 oz.
245/75	R22.5	C-8 oz.	B-10 oz.
265/75	R22.5	C-8 oz.	B-10 oz.
285/75	R22.5	B-10 oz.	A-12 oz.
295/75	R22.5	B-10 oz.	A-12 oz.
315/75	R22.5	A-12 oz.	V- 14 oz.
345/75	R22.5	A-12 oz.	
350/75	R22.5	V-14 oz.	
235/80	R22.5	D-6 oz.	C-8 oz.
255/80	R22.5	C-8 oz.	B-10 oz.
275/80	R22.5	B-10 oz.	A-12 oz.
295/80	R22.5	A-12 oz.	V-14 oz.
305/85	R22.5	A-12 oz.	V-14 oz.
315/80	R22.5	A-12 oz.	V-14 oz.
365/80	R22.5	V-14 oz.	
445/50	R22.5	W-16 oz.	
455/50	R22.5	W-16 oz.	
385/65	R22.5	A-12 oz. hwy	W-16 oz. flotation
425/65	R22.5	W-16 oz.	
435/45	R22.5	V-14 oz.	
445/55	R22.5	W-16 oz.	
445/65	R22.5	W-16 oz.	
495/45	R22.5	W-16 oz.	
15.00	R22.5	A-12 oz. hwy	W-16 oz. flotation
16.50	R22.5	W-16 oz.	



# EQUAL FLEXX

MORE MILES. LESS FUEL

## TRUCK TIRES (CONT.)

Tire Size		Wheel Position	
		Single	Dual
18.00	R22.5	W-16 oz.	
11.00	R24	A-12 oz.	V-14 oz.
12.00	R24	V-14 oz.	
14.00	R24	W-16 oz.	
285/75	R24.5	B-10 oz.	A-12 oz.
305/75	R24.5	A-12 oz.	V-14 oz.
315/75	R24.5	A-12 oz.	V-14 oz.
275/80	R24.5	B-10 oz.	A-12 oz.
295/80	R24.5	B-10 oz.	A-12 oz.
11.00	R24.5	B-10 oz.	A-12 oz.
12.00	R24.5	A-12 oz.	V-14 oz.



# EQUAL FLEXX

MORE MILES. LESS FUEL

## COMMERCIAL LIGHT TRUCK TIRES



The following tire sizes apply only to light truck tires (must be LT rated) for commercial vehicles with dual wheel positions and a 10,000 GVW rating (Class 3) or higher. Check your load capacity to identify the proper amount for your tires on the chart below.

Tire Size		Load Range	
		B, C, or D	E or Higher
195/70	R15	F-3 oz.	D-6 oz.
195/65	R16	F-3 oz.	D-6 oz.
305/70	R16	C-8 oz.	B-10 oz.
225/75	R16	E-4 oz.	D-6 oz.
245/75	R16	E-4 oz.	D-6 oz.
265/75	R16	D-6 oz.	C-8 oz.
285/75	R16	C-8 oz.	B-10 oz.
295/75	R16	C-8 oz.	B-10 oz.
315/75	R16	C-8 oz.	B-10 oz.
215/85	R16	F-3 oz.	D-6 oz.
225/85	R16	E-4 oz.	D-6 oz.
235/85	R16	E-4 oz.	D-6 oz.
245/85	R16	E-4 oz.	D-6 oz.
255/85	R16	D-6 oz.	C-8 oz.
265/85	R16	D-6 oz.	C-8 oz.
305/85	R16	B-10 oz.	A-12 oz.
7.50	R16	F-3 oz.	D-6 oz.
8.25	R16	E-4 oz.	D-6 oz.
11.00	R16	C-8 oz.	B-10 oz.
245/75	R17	D-6 oz.	C-8 oz.
265/70	R17	D-6 oz.	C-8 oz.
235/80	R17	E-4 oz.	D-6 oz.
315/70	R17	C-8 oz.	B-10 oz.

Tire Size		Load Range	
		B, C, or D	E or Higher
315/70	R17.5	C-8 oz.	B-10 oz.
195/60	R17.5	F-3 oz.	D-6 oz.
205/60	R17.5	F-3 oz.	D-6 oz.
225/60	R17.5	E-4 oz.	D-6 oz.
8.00	R17.5	E-4 oz.	D-6 oz.
8.50	R17.5	E-4 oz.	D-6 oz.
9.00	R17.5	D-6 oz.	C-8 oz.
10.00	R17.5	C-8 oz.	B-10 oz.
11.00	R17.5	B-10 oz.	A-12 oz.
14.00	R17.5	A-12 oz.	W-16 oz.
195/70	R17.5	F-3 oz.	D-6 oz.
215/70	R17.5	E-4 oz.	D-6 oz.
235/70	R17.5	E-4 oz.	D-6 oz.
205/75	R17.5	E-4 oz.	D-6 oz.
215/75	R17.5	E-4 oz.	D-6 oz.
225/75	R17.5	E-4 oz.	D-6 oz.
235/75	R17.5	D-6 oz.	C-8 oz.
205/80	R17.5	E-4 oz.	D-6 oz.
225/80	R17.5	E-4 oz.	D-6 oz.
225/90	R17.5	D-6 oz.	C-8 oz.
245/70	R18	D-6 oz.	C-8 oz.
275/65	R18	D-6 oz.	C-8 oz.



# EQUAL FLEXX

MORE MILES. LESS FUEL

## LIGHT TRUCK MUDDER APPLICATION CHART

Tire Size	Wheel Size	Size
33 x10.50	15	E-4 oz.
33x11.50	15	E-4 oz.
33x12.50	15	D-6 oz.
33x14	15	D-6 oz.
33x14.5	15	D-6 oz.
33x15.5	15	D-6 oz.
34x9.5	15	E-4 oz.
34x12.5	15	D-6 oz.
35x12.5	15	D-6 oz.
35x14.5	15	D-6 oz.
35x15	15	D-6 oz.
35x16	15	C-8 oz.
36x14.5	15	D-6 oz.
36x15.5	15	C-8 oz.
36x16.5	15	C-8 oz.
37x12.5	15	D-6 oz.
38x12.5	15	D-6 oz.
38.5x11	15	D-6 oz.
38.5x15.5	15	C-8 oz.
38.5x16	15	C-8 oz.
38.5x16.5	15	C-8 oz.
39x15	15	C-8 oz.
39.5x18	15	C-8 oz.
40x17	15	C-8 oz.
42x15	15	C-8 oz.
44x18.5	15	B-10 oz.
44x19.5	15	B-10 oz.
44x21	15	B-10 oz.
Q78	15	E-4 oz.
33x11.50	16	E-4 oz.
33x12.5	16	D-6 oz.

Tire Size	Wheel Size	Size
33x13	16	D-6 oz.
33x13.5	16	D-6 oz.
34x9	16	E-4 oz.
34x12.5	16	D-6 oz.
35x12.50	16	D-6 oz.
35x14.50	16	D-6 oz.
36x13	16	D-6 oz.
36x14	16	D-6 oz.
36x14.50	16	D-6 oz.
38x15.50	16	C-8 oz.
38.5x11.00	16	D-6 oz.
38.5x14.5	16	C-8 oz.
39.5x15	16	C-8 oz.
40x14.5	16	C-8 oz.
42x15	16	C-8 oz.
44x21	16	B-10 oz.
255/85	16	E-4 oz.
325/80	16.5	D-6 oz.
33x12.50	16.5	D-6 oz.
33x14.00	16.5	D-6 oz.
33x15.50	16.5	D-6 oz.
34x9.50	16.5	E-4 oz.
35x12.5	16.5	D-6 oz.
35x14.50	16.5	D-6 oz.
35x15	16.5	D-6 oz.
35x16	16.5	C-8 oz.
36x12.50	16.5	D-6 oz.
36x14.50	16.5	D-6 oz.
37x12.50	16.5	D-6 oz.
38x12.50	16.5	D-6 oz.
38x15.50	16.5	C-8 oz.

Tire Size	Wheel Size	Size
38.5x15	16.5	C-8 oz.
38.5x16	16.5	C-8 oz.
39.5x15	16.5	C-8 oz.
39.5x18	16.5	C-8 oz.
42x15	16.5	C-8 oz.
44x18.5	16.5	B-10 oz.
44x19.5	16.5	B-10 oz.
49x21	16.5	A-12 oz.
33x12.5	17	D-6 oz.
35x12.5	17	D-6 oz.
37x12.50	17	D-6 oz.
38x15.50	17	C-8 oz.
38.5x14.50	17	C-8 oz.
39.5x15	17	C-8 oz.
42x15	17	C-8 oz.
44x21	17	B-10 oz.
33x12.50	18	D-6 oz.
35x12.50	18	D-6 oz.
37x13.5	18	D-6 oz.
38x15.50	18	C-8 oz.
38.5x14.50	18	C-8 oz.
33x12.50	20	D-6 oz.
35x12.50	20	D-6 oz.
38.5x14.50	20	C-8 oz.
39.5x15	20	C-8 oz.
44x21	20	B-10 oz.
38x15.50	20	C-8 oz.
39.5x15	20	C-8 oz.
35x12.50	22	D-6 oz.

There are many variables that contribute to vibration in “mudder” tires. Before installing FLEXX, please consider the following sources of vibration, including but not limited to: Proper drive line angle, tire pressure, presence of a lift kit, tire run-out, wheel run-out, extreme side wall flex, tread ripple, and/or a lug pattern that may cause acoustical vibration. These factors, and others, will play a role in the vibration of the vehicle and FLEXX will not correct these conditions. We cannot guarantee the elimination of all vibration sources.